

## Pultruded grp scaffold tube specification

|                        |   |
|------------------------|---|
| PRODUCTS:              | GRP Pultruded Scaffold Tube   |
| RAW MATERIALS:         | Isophthalic polyester resin<br>E glass fibre roving, and continuous filament mat together with woven roving fabric as appropriate for the individual profiles<br>Polyester surface veil together with continuous filament glass fibre mat on all external surfaces  |
| COLOUR                 | Red RAL 3000 or yellow RAL 1004   |
| PRODUCT STANDARD:      | EN13706-2 and EN13706-3   |
| PRODUCT DIMENSIONS:    | 48.55mm od x 35mm id  |
| PRODUCT SPECIFICATION: | Profile manufacturer by the pultrusion process.<br>Fully complying with all the requirements of EN13706-2 including dimensional tolerances and quality assurance parameters.<br>Structural properties meeting the E23 grade of EN 13706-3 but with higher modulus - 30GPa and enhanced crush strength<br>ISO 9001 registered quality controlled production. |

[www.mills-scaffold.com](http://www.mills-scaffold.com)

**MILLS CONSTRUCTION PRODUCTS INC.**

13904 Hurontario St., Caledon, ON L7C 2B8 tel:(905) 451-9471 fax:(905) 838-4059



NON-CONDUCTIVE  
PULTRUDED GRP SCAFFOLD TUBE SPECIFICATION